



Analogue Bursting Strength Tester

Common Features : Single Push Button operation, Maximum pointer for peak value reading, Dual Gauges model for greater accuracy, Heavy duty bourdon pressure gauges.



BST - S2

Fully enclosed model, Panel mounted pressure gauges, Switch operated gauge selection through solenoid valve.

Capacity	0 – 40 kg/cm ²	
Measurement units	Kg/cm ² & PSI	
Pressure Gauges	2	
Gauge I	0 – 8 kg/cm ²	Least Count : 0.1 kg/cm ²
Gauge II	0 – 40 kg/cm ²	Least Count : 0.5 kg/cm ²
Power supply	230 Volts AC 50 Hz	
Dimensions in mm	700 x 500 x 400 - (L X W X H)	
Net Weight	80 kg	
Gross Weight	110 kg	

BST - N2

Open type model, body mounted pressure gauges, Manual selection of gauges through SS needle valve

Capacity	0 – 40 kg/cm ²	
Measurement units	Kg/cm ² & PSI	
Pressure Gauges	2	
Gauge I	0 – 8 kg/cm ²	Least Count : 0.1 kg/cm ²
Gauge II	0 – 40 kg/cm ²	Least Count : 0.5 kg/cm ²
Power supply	230 Volts AC 50 Hz	
Dimensions in mm	500 x 400 x 400 - (L X W X H)	
Net Weight	70 kg	
Gross Weight	100 kg	



Vertex Engineers & Associates

An ISO 9001:2008 Certified Company

Office Address: R.H. 116, Near Datta Meghe Engg. College, Sector 2B, Airoli, Navi Mumbai – 400708, Maharashtra, India

Telephone: +91-22-27791675 / +91-22-65169832 Tele-fax: +91-22-27791675

Email: info@vertexmachines.com, Web: www.vertexmachines.com

Factory Address: Milkat No. 665, At Nele Post Kidgaon, Dist. Satara 415 015, Maharashtra, India