



# VERTEX

## COATING THICKNESS GAUGE



These gauges can be used for non-destructive coating thickness measurement of non-magnetic coatings, e.g. paint, enamel, chrome on steel, and insulating coatings, e.g. paint and anodizing coatings on non-ferrous metals.

### FEATURES:

- 1m length separated probe
- Range 0~3000um, accuracy  $\pm 2\% \pm 1\mu\text{m}$
- 128\*128dots LCD display
- Menu interface
- Red LED alarm indication
- LCD shows mean, maximum, minimum and standard deviation User can set alarm limit
- Readings can be stored, recalled and deleted
- Easy to do zero calibration and support multi-point calibration Connect with PC via USB and download readings
- Multi-language supported
- Up to 5 measurement groups supported
- Automatically detect the substrates type (F or N)
- Unit optional: um, mm and mils

## ADDITIONAL INFORMATION:

- **Item Code:** Accu-3000FNF
- **Delivery Time:** Ready stock
- **Packaging Details:** Main unit, Probe, Calibration foil set, Software cable, software CD, Carry bag, user manual, calibration certificate

## SPECIFICATION:

Measuring Range	0-3000 um
Accuracy	1 % of reading
Resolution	0.1 um
Minimum Measurement Area	5 mm
Minimum Sample Thickness	0.2 mm
Least Count	0.1
Size	6 x 4
Color	Red and white
Usage/Application	Painting industries
Model Name / Number	ACCU3000FNF
Power Supply	3 x 1.5V AAA batteries
Type	F / NF



<https://www.vertexmachines.com/>



+91 93234 05785



info@vertexmachines.com

Actual product may differ in color and appearance due to constant development.