



# VERTEX

## DIGITAL COATING THICKNESS GAUGE Ferrous (Fe)



### Standard Features:

#### Technology:

- Latest technology with use of smart micro-controller.
- Direct Measurement - No Calibration Required for Most Of Surfaces.
- Highest Accuracy and Resolution.
- "Zero" and "SET" functions along with Foils and Zero base simplicities Calibration.
- Calibration Retaining System.

#### Probe Design:

- Fully Metallic / High Quality Plastic Probe For High Service Life.
- Well Balanced and Spring Loaded Probe for Accurate measurements.
- Ideal Probe design to take reading in complex Field Areas.
- Strong Wear-Resistant Tip For Extra Service Life.
- Highly flexible Probe cable with Strain relief.

#### Ergonomics

- Compact and Light Weight Instrument.
- Full ABS high impact resistant body.
- Attractive Instrument display and visuals.
- External battery Compartment.

#### Energy Efficient

- Auto-Off Function.
- Sun Readable and Energy Saving Display.

## Specification:

<b>Range (Microns)</b>	0-1500, 2000, 3000, 6000, 12000
<b>Resolution (Microns)</b>	0.1 < 20 Microns, 1 > 20 Microns
<b>Minimum Base Thickness</b>	0.3 MM
<b>Minimum Measuring Area</b>	6 MM
<b>Instrument Size</b>	135*70*24
<b>Battery Supply Voltage / type</b>	9 Volts (6F22)
<b>Working Temperature</b>	10-15 degree C
<b>Standard Probe Size</b>	18 MM * 14 MM (D*L)



<https://www.vertexmachines.com/>



+91 93234 05785



info@vertexmachines.com

Actual product may differ in color and appearance due to constant development.