

## **VERTEX**

# DIGITAL PORTABLE HARDNESS TESTER TIME 5100



## **STANDARD DELIVERY:**

Main Unit	1
Test Block HLD	1
USB connecting cable	1
Cleaning Brush	1
Battery AAA 1.5V	2
Time certification	1
Instuction manual	1
Warranty Card	1

### **Optional Accessories**

- Support rings
- Dataview software

#### **Features:**

- USB communication interface
- Automatic identification of impact test direction
- Memory of 270 average data in 9 group files
- Upper and lower limit setting
- Automatically switch off
- Backlight for convenient use in darkness
- Battery capacity display
- AAA 1.5V battery
- Integrated calibration function
- Time®5100: integrated with D impact device for normal hardness testing
- Time®5102: integrated with C impact device for hardness testing on thin, light and face-hardnened workpiece.
- Time®5104: integrated with DL impact device for hardness testing of deep grooves and tooth surface

## **Technical Specification:**

Model	Time®5100	Time®5102	Time®5104	
Impact Device	D integrated	C integrated	DL integraed	
Hardness Scales	HLD, HB, HRC, HRB,	HLC, HB, HRC, HRB, HV,	HLDL, HB, HRC, HRB, HV,	
	HV, HS	HS	HS	
Accuracy	±6HLD(760 ±30HLD)	±12HLC	±12HLDL	
Memory	270 average readings in 9 group files			
Output	RS 232 to printer	RS232 to printer	RS232 to printer	
Min. Surface	1.6µm (Ra)	0.4μm (Ra)	1.6µm (Ra)	
Roughness of				
work piece				
Max. work piece	900HLD	960HLC	950HLDL	
hardness				
Min. radius of	Rmin = 50mm (with	Rmin = 11mm (with	Rmin = 10mm(with	
work	support ring Rmin =	support ring)	support ring Rmin =	
piece(convex /	10mm)		10mm)	
concave)				


Min. Work piece weight	2~5kg on stable support 0.05~2kg with compact coupling	0.5~1.5kg on stable support 0.02~0.5kg with compact coupling	2~5kg on stable support 0.05~2kg with compact coupling	
Min. work piece thickness coupled	5mm	1mm	5mm	
Min. Thickness of hardnened layers	0.8mm	0.2mm	0.8mm	
Indentation depth	Impact devices data	Impact devices data	Impact devices data	
Continuous working time	150h (without backlight)			
Power	AAA 1.5V batteries			
Operating Temperature	0~40°C	0~40°C	0~40°C	
Overall dimensions(mm)	155 X 55 X 25	160 X 60 X 25	215 X 60 X 25	

#### **Online measurement**



#### Data analysis

#### Bar chart




DataView TH51X is a special software for TH51X series Hardness Tester.

The data stored in the Hardness Tester TH51X series can be downloaded to the PC for further analysis. It has online measurement mode and offline analysis mode, data analysis, graphics display and print output functions are all available.


## TIME®5100/5102/5104

**SOFTWARE** 


#### Curve Chart



#### Data sheet



#### Setting of Tolerance limit



#### Data report

